

LOGOCLIC®

SILENTOS

1285 x 192 x 7+2 mm

PACKAGE: 8 PANELS | 1.97 m² | 14 kg
www.blauer-engel.de/uz176

Support material: HDF, E1 low-swelling
glue-laminated
Density 830 – 900 kg/m³

Walking noise: 2 mm

Decorative layer: 0.2 mm



According to EN 13329 it is suitable for all living areas with intensive use and for commercial areas with moderate use

DIMENSION

dimension	thickness (d)	7+2 ± 0,50 mm · dmax - dmin ≤ 0,80 mm		
	length	1285 ± 0,50 mm		
	width (b)	192 ± 0,10 mm · bmax - bmin ≤ 0,20 mm		
profile	long side	twin clic	short side	twin clic



Empfohlen durch das

**SENTINEL HAUS
INSTITUT**

TOLERANCE

squareness	EN 13329	≤ 0,20 mm
straightness	EN 13329	≤ 0,30 mm
flatness crosswise	EN 13329	concave: ≤ 0,15% · convex: ≤ 0,20%
flatness length	EN 13329	concave: ≤ 0,50% · convex: ≤ 1,00%
gaps between elements	EN 13329	average: ≤ 0,15 mm · max: ≤ 0,20 mm
height difference between elements	EN 13329	average: ≤ 0,10 mm · max: ≤ 0,15 mm
misalignment		± 2 mm

TEST

abrasion resistance	EN 13329	AC3 (≥ 2000 rpm)
impact resistance	EN 13329	small ball ≥ 10 mm · big ball ≥ 500 mm
stain resistance	group 1 & 2	grade 5
	group 3	≥ grade 4
castor chair test	EN 13329	no change in appearance or damage, as defined per EN 425
effect of a furniture leg	EN 13329	no damage shall be visible, when tested with foot type 0
thickness swelling	EN 13329	≤ 18%
static indentation	EN 13329	≤ 0,05 mm
light fastness	EN 13329	grey scale ≥ 4 at blue wool grade 6
dimensional variations after changes in relative humidity	EN 13329	lengthwise ≤ 0,9 mm · crosswise ≤ 0,9 mm
surface soundness	EN 13329	≥ 1,0 N/mm ²

ENVIRONMENT

emission of formaldehyde	EN 16516	class E1
--------------------------	----------	----------

PHYSICAL BEHAVIOR

fire behavior	EN 13501-1	Cfl s1
slide resistance	EN 13893	technical class DS
walking noise emission	IHD-W431	24,4%
thermal resistance	EN 12667	0,116 (m ² K)/W ± 15%

The data sheet is updated regularly to meet new technological standards. This version replaces all previous versions as well as those which are undated.
This version takes effect upon creation. Version 05/2023

